
A
B
C
D
E
F
VALID
CYCLE 1
D4
D3
D2
D1
ACCEPT
VALID
CYCLE 2
D4
D3
D2
D1
ACCEPT
VALID
CYCLE 3
D4
D3
D2
D1
ACCEPT
VALID
CYCLE 4
D5
D4
D3
D2
D1
ACCEPT
VALID
CYCLE 5
D5
D4
D3
D2
ACCEPT
VALID
CYCLE 6
D5
D4
D3
D2
ACCEPT
H
L

FIG. 1



FIG. 2(A)



FIG. 2(B)



FIG. 3A-1



FIG. 3A-2



FIG. 3B-1



FIG. 3B-2


PH1
PH0
IN DATA (7:0)
8
D
Q
CK
LDIN
B1
LDOUT
B2
OUT DATA (7:0)
NOTRE SETO
R
IN_VALID
D
Q VIN
CK
LVIN
D
Q VOUT
CK
LVOUT
OUT VALID
IN_ACCEPT
Q AIN
D
CK
LAIN
NAND1
INV1
Q AOUT
D
CK
LAOUT
NAND2
INV2
OUT ACCEPT

FIG. 4


00 aa 55 33 00 cc 00 04 00 aa 55 33 cc 00
00 aa 55 33 00 cc 00 04 00 aa 55 33 cc
00 aa 55 33 cc 00 04 aa 55 33 cc
110 150 190 230 270 310 350 390 430 470 510 550 590 630
TIME

FIG. 5(A)


PH0
PH1
NOT_RESET
04
00
04
ff
00
IN_DATA
IN_VALID
IN_ACCEPT
00
04
ff
D_LDOUT
Q_{AIN}
Q_{AOUT}
cc
00
04
ff
OUT_DATA
OUT_VALID
OUT_ACCEPT
630 670 710 750 790 830 870
TIME

FIG. 5(B)


PH1
PHØ
IN_DATA(7:0)
D Q
CK Q̄
LDIN
MD(7:0)
MD(2)
N_MD(7:0)
D Q
CK
LDOUT
OUT_DATA(7:0)
NAND1
N_MD(7)
N_MD(6)
N_MD(5)
N_MD(4)
N_MD(3)
NAND2
SA
NOR1
D Q
CK
LADDR
DATA_ADDR
D Q
QEPREV
CK
LEPREV
IN_EXTN
D Q
CK
LEIN
D Q
CK
LEOUT
OUT_EXTN

FIG. 6


PH1
PHØ
LOE
LPREV
LAST_OUT_EXTN
LEIN
LEOUT
IN_EXTN
OUT_EXTN
ANDI
LVIN
LVOUT
IN_VALID
OUT_VALID
NOT_RESET
LAIN
LAOUT
IN_ACCEPT
OUT_ACCEPT
ORI
OR2
D
Q
CK
R

FIG 7


PH1
PHØ
IN_DATA(7:0)
D Q
CK
LD IN
MID-DATA(7:0)
MID-ACCEPT
IN_EXTN
LE IN
INV10
S4
NAND 10
NOT_RESET_O
IN_VALID
LV IN
INV12
NAND 12
S5
IN_ACCEPT
INV 16
NAND 16
LAIN
Q D
NAND 14
INV14
NOR1
MID-DATA (7)
MID-DATA (6)
MID-DATA (5)
MID-DATA (4)
MID-DATA (3)
MID-DATA (2)
NOR2
NAND18
S1
LI1
LI2
NAND20
S2
NAND22
LI3
S3
NAND24

FIG. 8(A)


D Q
CK
LD OUT
OUT_DATA(7:0)
D Q
CK
LE OUT
OUT_EXTN
MID-EXTN
NAND 30
INV30
OUT_VALID
D R Q
CK
LV OUT
NAND
28
INV
28
Q D
CK
LA OUT
OUT_ACCEPT
NAND
26
INV
26
56
LO1
LO2
DATA_TOKEN
LO3
NOT_DUPLICATE

FIG. 8(B)


00 aa cc 04 00 55 33 00 cc aa 33 00 04 08 00 04 55 00
00 aa cc 04 00 55 33 cc aa 33 00 04 08 04 55
00 aa cc 04 55 33 cc aa 33 00 04 08 04
143 208 273 338 403 468 533 598 663 728 793 858 923
TIME

FIG. 9(A)


PHØ
PH1
NOT_RESET
IN_EXTN
IN_DATA
IN_VALID
IN_ACCEPT
MID_EXTN
MID_DATA
MID_VALID
MID_ACCEPT
OUT_EXTN
OUT_DATA
OUT_VALID
OUT_ACCEPT
DATA_TOKEN
NOT_DUPLICATE
cc 00 33 00 aa 00
55 cc 00 33 00 aa 00
55 cc 00 33 00 aa 00
923 988 1053 1118 1183 1248 1313
TIME

FIG. 9(B)


43
44
Register
Register
46
Token
Decode
33
40
Action
Identification
39
32
37
38
Input
Latches
34
35
Processing Unit
36
Output
Latches
41
42
31

FIG. 10


State Machine
(ROM)
68
67
69
52
SCD
51
53
FIFO
54
55
Huffman
Decoder
56
63
I to D
64
65
ALU
66
70
T/F
71
72
FIFO
73
57
76
74
61
Dram
Interface
58
62
External
Dram
IMODEL
75
78
IQUANT
79
80
IZZ
81
82
IDCT
83
84
TO 92
(FIG.12)
77
60
Buffer
Manager
59

FIG. 11



FIG. 12



FIG. 13



FIG. 14a



FIG. 14b



FIG. 14c


H.261
MPEG
JPEG

FIG. 15


162
161
PICTURE-START
163
PICTURE-END
164
166
165
PICTURE-START
167
PICTURE-END
168

FIG. 16


EXTERNAL
DRAM
177
ADDRESS
GENERATOR
174
175
DRAM INTERFACE
176
190
178
PREDICTION
FILTERS
179
187
173
180
172
SPLIT
171
182
FIFO
183
184
+
181
185
WRITE
SIGNAL
GENERATOR
186
188
READ
SIGNAL
GENERATOR
189
191

FIG. 17


FORWARD
PREDICTION
FILTER
201
BACKWARD
PREDICTION
FILTER
204
202
205
+
203
206

FIG. 18



FIG. 19



FIG.20



FIG. 21


HEADER GENERATOR
263
262b
252
FLAG
GENERATOR
251
262a
262
266
253
256
DECODE
INDEX
257
258
EXTRA WORD
GENERATOR
264
262c
OUTPUT
LATCHING
265
259
254
261
260
272
268
273
269
271
270
267
274
255
283
285
284
278
279
282
280
281
277
276
275

FIG.22


ADDRESS GENERATOR
301
CONTROL
OTHER STAGES/ BLOCKS OF THE CHIP
WRITE
READ
EXTERNAL DRAM 303
DRAM INTERFACE 302

FIG.23



FIG.24



FIG. 25



FIG. 26


PARSER
STATE
MACHINE
322
328
INSHIFT
HUFFMAN
DECODER
INDEX TO DATA
ALU
TOKEN FORMAT
327
327
323
321
324
325
326

FIG.27


INPUT DATA
FORMAT
331
1-D PREDICTION
X-COORDINATE
332
DIMENSION
BUFFER
333
1-D PREDICTION
Y-COORDINATE
334
OUTPUT DATA

FIG.28


Multiplexed audio/video data
Audio / Video demultiplexor
Coded video data
Coded audio data
DRAM
Spatial Decoder
Spatial Decoder
DRAM
Temporal Decoder
Temporal Decoder
Control Microprocessor
DRAM
Image Formatter
Video Formatter
Audio Decoder
Raster video data

FIG.29



FIG.30



FIG.31



FIG.32


extension bit
bits 7:0
0
1
1
1
1
1
0
6 word Token
1 word Token
0
Start of Token
1
1
End of Token
0

FIG.33


extension bit
bits 7 ... 0
E
7
6
5
4
3
2
1
0
1
A
A
A
A
D
D
D
D
1
D
D
D
D
D
D
D
D
0
D
D
D
D
D
D
D
D
3 word Token
A
Address field
D
Data field

FIG.34



FIG.35



MPEG 4:2:0
macroblock

FIG.36A

JPEG 2:1:1
macroblock

FIG.36B


clock
valid
accept
data
1
2
3
TIME

FIG.37


Coded video data
DRAM
Spatial Decoder
DRAM
Temporal Decoder
Control Microprocessor
DRAM
Image Formatter
Raster video data

FIG.38


Decoder clock propagation
Oscillator
system de-mux
Spatial Decoder
Temporal Decoder
Image Formatter
Data propagation

FIG.39


Clock
valid / accept
data / extn
3
1
2, 4
3
1
2, 4
TIME

FIG.40


Access Start
Data Transfer
Default State

FIG.41


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.42


5
RAS
6
DRAM_addr[10:0]
WE
Row address timing
CAS[3:0]
OE
data[31:0]
Start of read
CAS[3:0]
OE
data[31:0]
Start of write
7
CAS[3:0]
OE
data[31:0]
Start of refresh
TIME

FIG.43



FIG.44


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.45


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
8
7
TIME

FIG.46


RAS
DRAM_addr[10:0]
CAS[3:0]
WE
OE
DRAM_data[31:0]
9
TIME

FIG.47


Hidden bits
High column address bits
Row address
Low column address bits
Byte select
23:22
21:15
14:6
5:2
1:0
8:0
Row address bits
10:4
3:0
Column address bits

FIG.48


10
12
11
Any signal
13
14

FIG.49


Any signal
15
16
17
18
Any other signal
TIME

FIG.50


Any bus
19
20
21
22
Any strobe
TIME

FIG.51


CAS[3:0]
23
24
DRAM_data[31:0]
TIME

FIG.52


25
26
enable[1]
enable[0]
27
28
addr[7:0]
rw
30
32
29
31
data[7:0]
TIME

FIG.53


25
26
enable[1]
enable[0]
27
28
addr[9:0]
rw
33
34
data[7:0]
TIME

FIG.54


8 bit value
16 bit value
32 bit value
bits[7:0]
bits[7:0]
bits[15:8]
bits[7:0]
bits[15:8]
bits[23:16]
bits[31:24]
base + 3
base + 2
base + 1
base + 0

FIG.55


DSM
Audio / Video demultiplexer
coded data clock
DRAM
Spatial Decoder
decoder clock
DRAM
Temporal Decoder
µP
µP clock
DRAM
Image Formatter
Audio Clock
Audio Decoder
Display
VTG
display clock

FIG.56


35
36
V_{IH}
V_{IL}
37

FIG.57


Off-chip DRAM
Coded data buffer
Token buffer
DRAM interface
Start-up control
Huffman decode and video demultiplex
Inverse modeler
Start code detection
Inverse quantiser
Input circuit
Inverse DCT
Coded video data
Microprocessor interface (MPI)
Error signal, motion vectors and other Tokens

FIG.58


Data bytes or Tokens via
Coded Data Port
Input
Circuit
Tokens to start code detector
Tokens via
microprocessor
interface

FIG.59


coded_clock
coded_valid
coded_accept
coded_data[7:0]
coded_extn
byte_mode
1
2
3
TIME

FIG.60


Non-data Tokens
Tokens from input circuit
Serial analysis of DATA Tokens for start codes
Additional Token insertion
Tokens to start-up control circuit

FIG.6 I


Long DATA Token
Start Code Detector
Start code detected and converted to Token
Short DATA Token

FIG.62


Non data Token inserted before start code
Start code in DATA Token
Start Code Detector

FIG.63


This looks like an MPEG picture start
0x00
0x00
0x01
0x00
0x00
0x01
0xB8
This looks like an MPEG group start

FIG.64


This looks like an MPEG slice start (0x28)
00000000 00000000 00000001 00101000 00000000 00000000 00001000
This looks like the prefix for a non-aligned MPEG start code

FIG.65


data discarded by discard all data or start code search
"new" video sequence
"old" video sequence
entry point for new video
end of "last" picture
filing system data blocks
FLUSH inserted to reset discard all mode

FIG.66


Detect end of picture and introduce PICTURE_END
Optionally stop after PICTURE_END and introduce a FLUSH following the PICTURE_END
Conditionally introduce SEQUENCE_START before PICTURE_START
Introduce CODING_STANDARD before SEQUENCE_START

FIG.67


Coded data buffer
Huffman decoder
Token buffer
From start code detector
Bit counter
Control logic
Output gate
To inverse modeller
Off-chip process

FIG.68


Coded data and Token buffers
D
C
B
A
Bit Counter
Enable Queue
Output Gate

FIG.69


Start code detector etc.
Coded data buffer
Huffman Decoder
Token buffer
Inverse Quantiser etc.

FIG.70


Buffer limit
Region of buffer holding valid data
Buffer base
Buffer length
0
Buffer read
Buffer number
Defined limits of one buffer
Physical limit of the DRAM array

FIG.71


Parser
Huffman Decoder
Macroblock Counter
ALU
Coded data and Tokens
from coded data buffer
Tokens to the Token
buffer

FIG.72


frame buffer
used by codec
horiz_macroblocks
a macroblock
valid area of
picture
vert_macroblocks

FIG.73



FIG.74A



FIG.74B



FIG.74C



FIG.74D

$$\begin{cases} \text{horiz\_macroblocks} = \dfrac{\text{horiz\_pels} + 15}{16} \\ \text{vert\_macroblocks} = \dfrac{\text{vert\_pels} + 15}{16} \end{cases}$$

FIG.75


From Token buffer
Run and Level representation of quantised coefficients
Inverse Modeller
Expanded to 8x8 blocks of quantised coefficients
Inverse Quantiser
8x8 blocks of coefficients
Inverse DCT
8x8 blocks of pixel information
To output of Spatial Decoder

FIG.76


Quantised values
Scale factor
Post Processing

FIG.77


Quantised values
Quantisation tables
Control logic
Post Processing

FIG.78


Scale factor
Quantised values
Quantisation tables
Post Processing
Control logic

FIG.79



FIG.80



FIG.81



FIG.82


Off-chip DRAM
DRAM interface
Form prediction address
Interpolate / filter prediction
Separate motion vectors
FIFO
Picture sequence control
Microprocessor interface (μPI)
Error signal, motion vectors and other Tokens
Block organised video data and other Tokens

FIG.83


Picture 1
Component 2
Picture 1
Component 1
Picture 1
Component 0
Picture 0
Component 2
Picture 0
Component 1
Picture 0
Component 0
component_offset_2
component_offset_1
component_offset_2
component_offset_1
picture_buffer_1
picture_buffer_0

FIG.84


Picture's
temporal
reference
0 3 1 2 6 4 5
I P B B P B B
Picture sequence in
coded data
0 1 2 3 4 5 6
I B B P B B P
Picture sequence
required for display

FIG.85



FIG.86



FIG.87



FIG.88


Picture buffer
Picture buffer
ΔP / I
previous P
or I

FIG.89


Picture buffer
Picture buffer
Motion vectors
Form
prediction
Error data

FIG.90


CODING_STANDARD
SEQUENCE_START
Sequence of pictures
FLUSH

FIG.91


picture layer
groups of blocks
macroblocks
blocks

FIG.92



FIG.93

CIF

0	1
2	3
4	5
6	7
8	9
10	11

QCIF

0
2
4

FIG.94



FIG.95

1	2	3	4	5	6	7	8	9	10	11
12	13	14	15	16	17	18	19	20	21	22
23	24	25	26	27	28	29	30	31	32	33

FIG.96


1
2
3
4
5
6
4 blocks of Y data
1 block of C_B data
1 block of C_R data

FIG.97


DATA 00
DATA 00
DATA 00
DATA 00
DATA 01
DATA 02
DATA 00
DATA 00
DATA 00
DATA 00
DATA 01
DATA 02

FIG.98

1	2	3	4	5	6	7	8
9	10	11	12	13	14	15	16
.							
.							
.							
59	58	59	60	61	62	63	64

FIG.99



FIG. 100



FIG. 101



FIG. 102



FIG. 103



FIG. 104



FIG. 105



FIG. 106


Picture's temporal reference
First GOP
Second GOP
0 3 1 2 6 4 5
I P B B P B B
10 13 11 12 16 14 15
2 0 1 5 3 4
I B B P B B
19 17 18 22 20 21
Picture sequence in coded data
0 1 2 3 4 5 6
I B B P B B P
10 11 12 13 14 15 16
0 1 2 3 4 5
B B I B B P
17 18 19 20 21 22
Picture sequence at display
Picture's "frame number"
Picture 17 may depend on 16 and 19

FIG. 107

FIG. 108



FIG. 109



FIG. 110



FIG. 111



FIG. 112



FIG. 113



FIG. 114



FIG. 115



FIG. 116



FIG. 117


Parser State Machine
In Shift
Huffman Decoder
Index to Data
ALU
Token Formatter

FIG. 118


Read AC Coefficients
Decode Tcoeff VLC
Index = ESCAPE ?
Y
N
Read 6 bit FLC
Index = EOB ?
Y
N
Accept New Command
Read 1 bit FLC
Read 1 bit FLC
0 ?
Y
N
Read 7 bit FLC
Read 7 bit FLC
0 ?
Y
0 ?
Y
N
N
Read 8 bit FLC
Read 8 bit FLC

FIG. 119


Command from Demux
next bit
Huffman
Decode Logic
= EOB
= ZRL
Huffman
State Machine
Index to Data
SSSS
RUN
ALU
SIGN, LEVEL
RUN

FIG. 120



FIG. 121A



FIG. 121B



FIG. 122



FIG. 123


Command from Demux
next bit
Huffman
Decode Logic
= EOB
= ESCAPE
= 0
Huffman
State Machine
Index to Data
LEVEL or SIGN
or 7, 8 bit FLC
RUN
ALU
SIGN, LEVEL
RUN

FIG. 124


35
not_reset
ph0
ph1
microinstruction
2-wire i/f
2-wire i/f
1
6
run
hardwired registers
1 x7
1
HUFF ALU
12
input data
17
output data
input ext
output ext
7
8
condition codes
constant
(token bus)
cc valid
change detect
upi request
upi enable
upi data
upi addr
8
7

FIG. 125


8
2-WIRE i/f
12
6
CONSTANT
INPUT DATA
RUN
EXT
ph0
INPUT BLOCK 400
ZERO DETECT
SCC
ZCC
SIGN
TO UPI
ZERO
CC VALID
CONDITION CODES 402
A REGISTER 403
ADD
INPUT
SGX
PEG
ph1
ph0
12
A
8
TO UPI
RUN 404
INPUT
ADD
6
RUN
6
TO UPI
A
REG
INPUT
ZERO
CONST
A
INPUT
INPUT1
+/-
INPUT2
405
12
ADD
INPUT
A
CONST
A
REG
RUN
DATA
SIGN
EXTEND
SIZE
406
12
SGX
SIGN
LEVEL
2-WIRE i/f
INPUT
A
ADD
ADDU4
SIGN
GND
S
17
RUN
RUN
GND
EXT
ph1
OUTPUT BLOCK 401
HARDWIRED MB
COUNTER STRUCTURE
ADDR
UPI ADDR
ADDRESS DECODE
ADD
SGX
UPI
12
12
REG
ph1
ph0
8
TO UPI
REGISTER FILE 407

FIG. 126


bmprtize
bminstr
bmrecalc
bmsnoop
REQ
ACK
To DRAM interface
Addresses

FIG. 127



FIG. 128



FIG. 129



FIG. 130


Address Generator
420
Data
Data
External
DRAM
422
DRAM Interface
421

FIG. 131


valid/accept
Control
Write Address
Read Address
RAM 1
Data In
430
Data Out
RAM 2

FIG. 132



FIG. 133



FIG. 134


BodyWord counter
63WordsInBody
TokenHeader
HeaderExtn
ExtnBit
PLA
NextSubstate
Address
Read/Write
Enable
InsertNext
CoefficientIs?

FIG. 135


Y[0]
Y[4]
Y[2]
Y[6]
Y[1]
Y[5]
Y[3]
Y[7]
c1s
c3s
c3s
c1s
√2
c1s
c3s
c3s
c1s
d1
d3
d7
d5
X[0]
X[1]
X[3]
X[2]
X[7]
X[6]
X[4]
X[5]
Key:-
coef
constant coefficient multiplier
adder,subtractor

FIG. 136



FIG. 137



FIG. 138


12
12 bit integer
decheck
DATA Error Checking and
Recovery
440
12
izz
Inverse Zig-Zag RAM
441
12
ip_fmt
Input Formatter
442
22
10 bits fraction
oned
1-D IDCT Transform
443
1st Dimension
22
7 bits fraction
tram
Inverse Zig-Zag RAM
444
22
oned
1-D IDCT Transform
445
2nd Dimension
22
4 bits fraction
ras
Round and Saturate
446
9
9 bit integer

FIG. 139


12
12 bit integer
decheck
12
uP port
izz
12
ip_fmt
22
10 bits fraction
uP port
snooper
22
oned
1st Dimension
22
7 bits fraction
uP port
tram
22
oned
2nd Dimension
22
4 bits fraction
uP port
snooper
22
ras
9
9 bit integer
uP port
super snooper
9

FIG. 140





NOTE: "COMMON BLOCK" IS ENTIRELY COMBINATIONAL (NO LATCHING)

FIG. 141


DRAM Interface
Address Generator 452
Prediction Filters 454
Micro Interface 459
Clock Generators
JTAG 460
Input Inter-face 450
Top Fork 451
FIFO 453
Predic-tion Adder Adder 455
Write Rudder Adder 457
Read Rudder Adder 456
Input
Output Inter-face Adder 458

FIG. 142


in_data
in_valid
in_accept
ph1
ph0
ck
ck
ck
ck
ck
ck
Logic
out_data
out_valid
out_accept

FIG. 143


Token Input
Token Decode
Macroblock Counter
Block Calculation
Base Block Address
Vector Offset
Reorder Read Requests
Write Requests
Prediction Requests
DRAM Interface

FIG. 144



FIG. 145



FIG. 146


Input Data
Pred. Filters Formatter
1-D Prediction Filter (x)
Dimension Buffer
1-D Prediction Filter (y)
Output Data

FIG. 147



FIG. 148

0	1	2	3	4	5	6	7
8	9	10	11	12	13	14	15
16	17	18	19	20	21	22	23
24	25	26	27	28	29	30	31
32	33	34	35	36	37	38	39
40	41	42	43	44	45	46	47
48	49	50	51	52	53	54	55
56	57	58	59	60	61	62	63

FIG. 149


Reorder Input
Token Input
FIFO 1
FIFO 2
Output
Token Decode
Token Input Control
FIFO Input Interface
Output Control

FIG. 150



FIG. 151



FIG. 152

Read Cycle



FIG. 153

Write Cycle



FIG. 154

SCANNED, # 94



FIG. 155


ph0
ph1
pic_clk
pic_ph0
prev_pic_ph0
prn_chg
en_prnum
new_incr_prn
incr_prn
prnum
pres_flag
For convenience pic_clk is shown simply re-timed to ph0; in reality this is properly synchronised.
pres_num
pres_num+1
state = PRES0
or TOKEN
TIME

FIG. 156



FIG. 157


PRESO
increment
index
PRES1
!pres_flg | allocated
DRQ
TOKEN
pic_start | flush | !valid | !accept

FIG. 158



FIG. 159A



FIG. 159B



FIG. 159C


BUFFER_BASE0 = 0
DISP_COMP_OFFSET0
0
1
2
3
4
2A
2B
2C
2D
2E
2F
57
DISP_HBS_COMP0
0x24 blocks
DISP_VBS_COMP0
5D8
602
603
604
605
62D
62E
62F
ADDR_HBS_COMP0

FIG. 160

BUFFER OFFSET 0x00

COMPONENT OFFSET 0x000 + ...

00	01	02	03	04	05	06	07	08	09	0A	0B
0C	0D	0E	0F	10	11	12	13	14	15	16	17
18	19	1A	1B	1C	1D	1E	1F	20	21	22	23
24	25	26	27	28	29	2A	2B	2C	2D	2E	2F
30	31	32	33	34	35	36	37	38	39	3A	3B
3C	3D	3E	3F	40	41	42	43	44	45	46	47
48	49	4A	4B	4C	4D	4E	4F	50	51	52	53
54	55	56	57	58	59	5A	5B	5C	5D	5E	5F
60	61	62	63	64	65	66	67	68	69	6A	6B
6C	6D	6E	6F	70	71	72	73	74	75	76	77
78	79	7A	7B	7C	7D	7E	7F	80	81	82	83
84	85	86	87	88	89	8A	8B	8C	8D	8E	8F

FIG. 16 1A

COMPONENT1 OFFSET 0x100 + ...

00	01	02	03	04	05
06	07	08	09	0A	0B
0C	0D	0E	0F	10	11
12	13	14	15	16	17
18	19	1A	1B	1C	1D
1E	1F	20	21	22	23

FIG. 16 1B

COMPONENT1 OFFSET 0x200 + ...

00	01	02	03	04	05
06	07	08	09	0A	0B
0C	0D	0E	0F	10	11
12	13	14	15	16	17
18	19	1A	1B	1C	1D
1E	1F	20	21	22	23

FIG. 16 1C


BU_WADDR_COMP0_LAST_MB_IN_HALF_ROW
BU_WADDR_COMP0_LAST_MB_IN_ROW
0 1 2 3 4 14 15 16 17 18 19 2A 2B
2C 2D 2E 2F 40 41 42 43 44 45 57
BU_WADDR_COMP0_BLOCKS_PER_MB_ROW=BU_WADDR_COMP0_HBS*(BU_WADDR_COMP0_MAXVB+1)
BU_WADDR_COMP0_LAST_ROW_IN_MB
BU_WADDR_COMP0_LAST_MB_ROW
Buffer0, Component 0
(BU_WADDR_BUFFER0_BASE=0, BU_WADDR_COMP0_OFFSET=0)
5D8 602 603
604 605 62D 62E 62F
BU_WADDR_MBS_HIGH
BU_WADDR_COMP0_MAXVB+1
BU_WADDR_COMP0_HALF_WIDTH_IN_BLOCKS
BU_WADDR_COMP0_MAXHB+1
BU_WADDR_MBS_WIDE
BU_WADDR_COMP0_HBS

FIG. 162



BLOCK ADDRESS=0+0+0x5D8+0x28+0x2C+1=0x62D

FIG. 163A



BLOCK ADDRESS=0+0+0+0x2A+0+0=0x2A

FIG. 163B


IDLE
idr data
idr define samp
fc
!ivr
idr codstd
idr pic start
!ivr
ADDR1
COD_STD
PIC_ST1
HSAMP
fc
idr other
comp!=2
ADDR2
PIC_ST2
VSAMP
!(ivr&!ixr)
idr hmbs
fc
comp!=2
OUTPUT_TAIL
ADDR3
PIC_ST3
idr vmbs
fc
!ivr
!ivr
ADDR4
HORZ_MBS1
VERT_MBS1
fc+!aar
!ivr
!ivr
ADDR5
HORZ_MBS0
VERT_MBS0
fc
HB
fc.!z
MB0
OTHER
fc
z
= return to IDLE
fc = first cycle
z = zero flag
MB1
fc.!z
!(ivr&rar&!ixr)
MB2
DATA
fc
z
!z&!H261%!fc
MB3
**
fc
MB4
MB4A
z&H261&!QCIF&
!mod3eq2
z&!mod
3eq2
fc
z
MB5
MB4B
!z&!fc
!z&H261&!QCIF&!fc
fc
z&mod3eq2&!tc
MB6
fc
MB4C
fc
MB4D
** = !z&!H261&fc+!z&H261&(QCIF+fc)+z&H261&QCIF

FIG. 164


UPI_DATA_BUS
LOADA_0
LOADB_0
UPI_WRITE_STROBES
PH1
UPI_WRITE_STROBES
DRIVEA_SELECTS
DRIVEB_SELECTS
UPI_BYTE_SELECTS
NUPIO[7:0]
VARIOUS CONSTANTS
SRCA[0]
SRCA[1]
SRCA[2]
SRCA[3]
SRCA[4]
SRCA[5]
SRCB[0]
SRCB[1]
SRCB[2]
SRCB[3]
SRCB[4]
SRCB[5]
COUT
C
D
CK
PHO
FC
R
D
C
CIN
PHO
N
U
CBUS[17:0]

FIG. 165



FIG. 166



FIG. 167



FIG. 168


x0
L
c01
c11
Register
Register
x1
L
R
c02
c12
Adder
Adder
Register
Register
x2
L
R
R
c03
c13
Adder
Adder
Register
Register
c04
c14
Add & Resolve
Add & Resolve
Register
Register
Saturate
Saturate
Latch
Latch
out_data0
out_data1

FIG. 169